

SYNCREX SERIES

Swiss-Style Production Turning Machines

[20/7 | 20/8 | 20/9 & 20/9X | 25/7 | 25/8 | 25/9 & 25/9X]



SYNCREX SERIES

Features and Benefits

- 20 mm and 25 mm models include standard 10,000 rpm main and sub spindles
- Machines run full bar capacity with no special bar end prep
- Spline-connected sliding head spindle for greater accuracy and less material waste
- Removable guide bushing adapter enables operators to preset guide bushing outside the machine
- Exclusive Mazak Auto Tool Setter in the machine reduces setup time
- Mazak HDCC machine base for increased machine stability and rigidity




Renowned Mazak quality and performance – backed by Mazak's industry-leading MPower Complete Customer Care

- | | |
|---|---|
| <ul style="list-style-type: none">2-year comprehensive warrantyEasy access to Mazak application expertsQuick parts availabilityExpert spindle rebuild and repair | <ul style="list-style-type: none">Live 24-hour supportMy Mazak online service portalRemote Assist serviceIn-depth training resources |
|---|---|


20 & 25 mm 7-Axis Model Tooling Configuration

- 11 OD turning stations (1/2" tool capacity)
- 3 cross drill live tool units (6,000 rpm)
- 8 boring bar stations (4 main/4 sub)
- 2 deep hole drill stations
- 4 back working static holders





20 & 25 mm 8-Axis Model Tooling Configuration

- 11 OD turning stations (1/2" tool capacity)
- 3 cross drill live tool units (6,000 rpm)
- 8 boring bar stations (4 main/4 sub)
- 2 deep hole drill stations
- Back working Y2 axis – 4 static holders; 4 rotating holders (6,000 rpm)



20 & 25 mm 9-Axis Model Tooling Configuration

- 8 OD turning stations (1/2" tool capacity)
- 3 cross drill live tool units (6,000 rpm)
- 8 boring bar stations (4 main/4 sub)
- 2 deep hole drill stations
- Back working Y2 axis – 4 static holders; 4 rotating holders (6,000 rpm)
- Positionable B-axis live tool unit – 3 main and 3 sub live tool units (9,000 rpm). Full contouring B axis optional



Mazak High-Damping Composite Casting (HDCC)

- | | |
|--|--|
| <ul style="list-style-type: none">Solid one-piece castingMachine base weighs 3,200 lbs10% more rigid than cast ironSuperior vibration damping characteristics | <ul style="list-style-type: none">80% less vibration at the cutting point30% longer tool lifeLess thermal distortion |
|--|--|

Standard and Optional Machine Specifications

		20/7	20/8	20/9 & 20/9X	25/7	25/8	25/9 & 25/9X
Machining Capacity	Max. Turning Diameter	0.7500" (20 mm)			1.0" (25 mm)		
	Max. Turning Bar Length (one chucking)	8.07"/205 mm					
	Max. Main Spindle Drilling/Tapping	0.390" (10 mm)/M10			0.390" (10 mm)/M12		
	Max. Backend Face Drilling/Tapping	0.390" (10 mm)/M10			0.390" (10 mm)/M12		
	Max. Cross Drilling/Tapping	0.390" (10 mm)/M8					
Capability	Main Spindle Speed	25 to 10,000 rpm					
	Sub Spindle Speed	25 to 10,000 rpm					
	C-Axis Main and Sub-Spindle	Full C Axis (0.00010°)					
	Max. Cross Live Tool Spindle Speed	6,000 rpm					
	Total No. of Tools Standard	29	33	36	29	33	36
	OD/Cross Live Tool/Back Working	11/4/4	11/4/8	8/4/8	11/4/4	11/4/8	8/4/8
	End Working Tools	2					
	Boring Bar Holder (Main/Sub)	4/4					
	B-Axis Tool (Main/Sub)	O		3/3	O		3/3
	B-Axis Contouring	-		9x only	-		9x only
	Turning Tool Size	1/2"					
	Rapid Traverse (X1, Y1, Z1, X2, Y2, Z2)	1377 ipm - 35 m/min					
	CNC Control	MAZATROL SmoothSt	S		S (20/9)	S	
MAZATROL SmoothStX		-		S (20/9X)	-		S (25/9X)
Motors	Main Spindle (40% ED)	5 hp (3.7kW)			8 hp (5.5kW)		
	Sub Spindle (40% ED)	5 hp (3.7kW)			8 hp (5.5kW)		
	Cross Drill Live Tools	6,000 RPM 1.4 HP / 1.0 kW					
	Back End Face Tools	6,000 RPM 1.3 HP / 0.9 kW					
Services	Coolant Tank Capacity	39 gallons (145 L)					
	Coolant Type	Non-water-soluble cutting oil/Water-soluble cutting fluid					
	Air Supply	72.5 psi (0.5 Mpa)					
	kVA (peak)	31.5	32.25	33.25	31.5	32.25	33.25
Dimensions	Center Height	41.34" (1050 mm)					
	Length	88.58" (2250 mm)					
	Width	48.23" (1225 mm)					
	Height	66.93" (1700 mm)					
	Machine Weight	7,850 lbs (3560 kg)					

- Not Available O Optional S Standard

MAZAK CORPORATION NORTH AMERICAN MANUFACTURING HEADQUARTERS

8025 Production Drive, Florence, KY 41042
Tel: (859) 342-1700

www.MazakUSA.com
www.MazakCanada.com

- Specifications are subject to change without notice. This product is subject to all applicable export control laws and regulations.
- The accuracy data and other data presented in this catalog were obtained under specific conditions.
- They may not be duplicated under different conditions. (room temperature, workpiece materials, tool materials, cutting conditions, etc.)
- Unauthorized copying of this catalog is prohibited.

